

Instructions for installing the Air Filter/Oil-Removal Kit: #004-579

ATTACH BRACKETS TO
WALL OR BENCH

NOTE: BRACKETS ARE
UNIVERSAL AND CAN BE
ATTACHED TO BEST FIT
YOUR NEEDS

ATTACH FILTERS TO
BRACKETS WITH
SCREWS SUPPLIED

AIR FLOW


AIR SOURCE
INLET

CHOOSE
DESIRED
BRASS
FITTING

MOISTURE /
DIRT FILTER
(WHITE)

AIR SOURCE
OUTLET
(TO ENGRAVING
MACHINE)

CHOOSE
DESIRED BRASS
FITTING



OIL REMOVAL
FILTER
(GREEN)

DRAIN STEM
PURGE FREQUENTLY

**CHANGE FILTER
WHEN DIRTY**

- #002-364
MOISTURE / DIRT FILTER
(WHITE)
- #002-633
OIL REMOVAL FILTER
(GREEN)

**REPLACE BOWL
IF BROKEN**

- #002-417
DRAIN BOWL

IMPORTANT
AIR FLOW DIRECTION
INDICATED BY ARROW
ON FILTERS



900 Overlander Road
Emporia, KS 66801

Toll Free: 800-835-3519

Phone: 620-343-1084

Fax: 620-343-9640

e-mail: GRS@GrsTools.com