

**NORMAL OPERATING RANGE**


10-13 psi (0.7-0.9 bar) / 2000 - 5000 strokes per min.

**RECOMMENDED INITIAL SETTING**

11 psi (0.8 bar) / 3000 strokes per min.



**ADJUSTING THE HANDPIECE**

The handpiece knob and barrel body are threaded together to allow adjustment of the overall handpiece length. The length can be adjusted from 4" - 4.25". While firmly holding the knob, loosen the locking ring. To lengthen, firmly hold the barrel and unthread the knob to the desired position. To shorten, firmly hold the barrel and unthread the locking ring to the desired position. Finally, thread the locking ring or knob together and tighten. *NOTE: Extending the overall length may cause a loss of power.*



**HOW TO ATTACH NEW HOSE**


Loosen the locking ring and remove the knob from the handpiece. Remove the old hose simply by cutting it off close to the knob. With a small punch, push the hose/brass fitting back into the knob body. Remove the brass fitting (#004-422 Air Hose Retainer) from the cut off hose piece. Feed the new air hose through the hole in the knob (FIG. 1). Insert the brass fitting into the end of the hose making sure it is fully seated. Moistening the fitting first may help it slip into the hose easier. Then apply a small amount of moisture around the outside end of the hose next to the brass fitting and pull the




hose back (FIG. 2) into the knob until you see the tip of the brass fitting protrude through the side of the knob. This must be an air-tight fit, so you will have to pull somewhat hard (a few pounds, at least).

**MAINTENANCE**


The only basic maintenance for the GRS Maestro Handpiece is keeping it clean on the inside. Problems will occur if oil or moisture gets into the handpiece, especially on the piston. If you notice a loss of power or erratic performance, the FIRST THING to check is to make sure the RECEIVER (chuck) IS TIGHT IN THE HANDPIECE BODY. Using a crescent wrench or pliers with a graver inserted in the QC Holder, gently tighten receiver clockwise (FIG. 3) If erratic performance continues, disassemble and clean the handpiece.



To disassemble the handpiece, use the crescent wrench or pliers to grip the graver (FIG. 3) and turn it counterclockwise to loosen the chuck retainer.




After loosening you can turn the chuck retainer out with your fingertips (FIG. 4). As you pull out the chuck, there will be a spring and piston.



Loosen the locking ring and remove it (FIG. 5).

Grip the knob and turn the handpiece body counter-clockwise until it is out of the knob body (FIG. 6).



With the handpiece disassembled, clean the parts with a non-residue solvent like denatured alcohol. Make sure the holes in the handpiece body are clear from dirt and debris. DO NOT allow moisture in the air hose. Before reassembly, make sure everything is dry.


DO NOT OIL INSIDE THE HANDPIECE. NO LUBRICANT IS REQUIRED. Lubricant will actually decrease performance!

**REASSEMBLY NOTE:**

There is an O-ring inside the knob that makes getting the handpiece body to thread a little difficult when reassembling. Use a very small amount of synthetic lube to create a thin film around the OUTSIDE of the shaft between the threads and the end (see VERY LIGHT in FIG. 7).


Do not use petroleum-based oils. Use **synthetic oils only**. Fossil oils can damage the O-Rings.

FIG. 7



**GRS<sup>®</sup> Maestro<sup>™</sup> Handpiece**

For any GRS GraverMach<sup>®</sup>, GraverMax<sup>®</sup>, GraverSmith<sup>®</sup>, or GraverMate<sup>®</sup>  
PARTS LIST • #004-947



Part No.	Description
002-590	O-Ring
002-605	Allen Wrench
002-903	O-Ring
004-416	Locking Nut
004-417	Handpiece Body
004-422	Air Hose Retainer
004-423	Air Hose - 1/8" dia. X 38"
004-424	Spring

Part No.	Description
004-803	QC Tool Holders (6)
004-927-V2	Piston / Hammer
004-929-V2	Maestro Receiver V2
022-072	Tube Coupling
022-082	Air Hose 10"
022-308	O-Ring 8 mm ID X 1 mm Wide
044-010	Handle Knob
044-251	Rubber Finger Grip

**GLENDO LLC**

900 Overlander Road • Emporia, KS 66801 USA  
800-835-3519 • 620-343-1084 • Fax: 620-343-9640  
glendo@glendo.com • www.grstools.com  
Last update: 03/24/2020